



Flatpack2

Rectifier Module 48/2000

Versatile and powerful solution for any application

The combination of cost-effective design, power density and reliability makes the Flatpack2 a product family that truly stands out and provides unparalleled network availability. The versatility of the Flatpack2 rectifier means that it can be used in a wide variety of 48VDC and 24VDC applications across the globe.

Applications

Wireless, fiber and fixed line communication

Today's communications demand state of the art, cost effective and compact DC power systems. Flatpack2 delivers an industry leading power density and superb reliability at lowest lifetime cost

Broadband and network access

Increasing network speed demands flexible and expandable DC power solutions. The Flatpack2 rectifiers are your key building blocks for future needs.

Small and large

Due to the high power density, cost competitive design and a highly flexible system communication interface, Flatpack2 rectifiers are used in system solutions from 5kW to 96kW.

Product Description

The Flatpack2 is a battery charger and rectifier for stand-alone use or for working in parallel as part of a DC power system controlled and monitored by the Smartpack.

Flatpack2 is optimized for a wide range of system sizes. Digital communication over CAN bus with Smartpack simplifies system design and enhances flexibility.

Realization of Flatpack2 systems is possible by fitting 4 rectifiers across a 23" or 19" shelf.

Key Features

Highest efficiency in minimum space

Resonant topology makes the module efficiency industry leading and contributes to the rectifier's ultra compact dimensions.

Digital controllers

Primary and secondary controls are digitalized, enabling excellent monitoring and regulation characteristics. Thus, the number of component has been reduced by 40% - for highly reliable, long life, trouble free DC power systems.

Heat management

Front-to-back air flow with chassis-integrated heat sinks gives the module the most suitable working environment and no limitations in the scalability of the desired system solution.

Unique connection

A true plug-and-play connection system: time-to-install and cost-reducing solution.

Global approvals

Flatpack2 is CE marked, UL recognized and NEBS certified for worldwide installation.

Flatpack2 Rectifier Module 48/2000

Additional Technical Specifications

| AC Input | |
|------------------|--|
| Voltage | 85-300 VAC (Nominal 185 – 275 VAC) |
| Frequency | 45 to 66Hz |
| Maximum Current | 12.5 Arms maximum at nominal input and full load |
| Power Factor | > 0.99 at 20% load or more |
| Input Protection | <ul style="list-style-type: none"> ○ Varistors for transient protection ○ Mains fuse in both lines ○ Disconnect above 300 VAC |

| DC Output | |
|----------------------------|--|
| Voltage | 53.5 VDC (adj. range: 43.5-57.6 VDC) |
| Output Power | 2000 W at nominal input |
| Maximum Current | 41.7 Amps at 48 VDC and nominal input |
| Current Sharing | ±3% from true average current between modules |
| Static voltage regulation | ±0.5% from 10% to 100% load |
| Dynamic voltage regulation | ±5.0% for 10-90% or 90-10% load variation, regulation time < 50ms |
| Hold up time | > 20ms; output voltage > 43.5 VDC at 1500W load |
| Ripple and Noise | <ul style="list-style-type: none"> ○ < 100 mV peak to peak, ○ 30 MHz bandwidth ○ < 0.96 mV rms psophometric |
| Output Protection | <ul style="list-style-type: none"> ○ Overvoltage shutdown ○ Blocking diode ○ Short circuit proof ○ High temperature protection |

| Other Specifications | |
|----------------------|--|
| Efficiency | Typical 92%, min. 91% at 40-90% load |
| Isolation | 3.0 KVAC – input and output 1.5 KVAC – input earth 0.5 KVDC – output earth |
| Alarms: | <ul style="list-style-type: none"> ○ Low mains shutdown ○ High temperature shutdown ○ Rectifier Failure ○ Overvoltage shutdown on output ○ Fan failure, one or two fans. ○ Low voltage alarm at 43.5V ○ CAN bus failure |
| Warnings: | <ul style="list-style-type: none"> ○ Low temperature shutdown ○ Rectifier in power derate mode ○ Remote battery current limit activated ○ Input voltage out of range, flashing at overvoltage ○ Loss of CAN communication with control unit, stand alone mode |
| Visual indications | <ul style="list-style-type: none"> ○ Green LED: ON, no faults ○ Red LED: rectifier failure ○ Yellow LED : rectifier warning |
| Operating temp | -40 to +75°C (-40 to +158°F) |
| Storage temp | -40 to +85°C (-40 to +185°F) |
| Cooling | 2 fans (front to back airflow) |
| Fan Speed | Temperature and current regulated |
| MTBF | > 350, 000 hours Telcordia SR-332 Issue I, method III (a) (Tambient : 25°C) |
| Acoustic Noise | < 55dBA at nominal input and full load (Tambient < 30°C) |
| Humidity | Operating: 5% to 95% RH non-condensing Storage: 0% to 99% RH non-condensing |
| Dimensions | 109 x 41.5 x 327mm (wxhxd) (4.25 x 1.69 x 13") |
| Weight | 1.9 kg (4.19lbs) |

| Applicable Standards | |
|----------------------|---|
| Electrical safety | IEC 60950-1 UL 60950-1 CSA 22.2 |
| EMC | ETSI EN 300 386 V.1.3.2 (telecommunication network) EN 61000-6-1 (immunity, light industry) EN 61000-6-2 (immunity, industry) EN 61000-6-3 (emission, light industry) EN 61000-6-4 (emission, industry) Telcordia NEBS GR1089 CORE |
| Mains Harmonics | EN 61000-3-2 |
| Environment | ETSI EN 300 019-2 (-1, -2, -3) ETSI EN 300 132-2 Telcordia NEBS GR63 CORE Zone 4 RoHS compliant (pending) |

Specifications are subject to change without notice

241115.100.DS3 – v3

Ordering Information

| Part no. | Description |
|------------|------------------------------------|
| 241115.100 | Flatpack2 Rectifier Module 48/2000 |

